



[www.decorativeconcreteofvirginia.com](http://www.decorativeconcreteofvirginia.com)

### Formal Quote

#### Frito Lay

The following is a proposal for the polished concrete with the Retro plate system which included with the system is a 10 year warranty on the floor. This warranty is only guaranteed through certified Retro plate installers. Below is a step by step process we have based the quote on as well as a Retroplate link and price based on approximately 6250 +/- square feet. Below is the step by step process of the project based on our discussion. It is our understanding that this is to be a turn key project that will be clean and ready for Frito Lay to enter the space upon completion.

#### **Carpet Removal**

- Remove all carpet in areas to be polished.
- Remove all cove base in areas to be polished
- Dispose of carpet and cove base in dumpster provided by DCVA

#### **Step-by-Step Polished Floor:**

- Grind with an 30/40-grit metal bond diamond to remove carpet glue on floor
- Grind with an 60/80-grit metal-bonded diamond.
- Grind with a 50 grit resin-bond
- Polish with a 100/200-grit resin-bond diamond.
- Polish with a 400-grit resin-bond diamond.
- Apply dye if desired (please see additional pricing)
- Apply Retroplate a chemical hardener to densify the concrete
- Polish with an 800-grit resin-bond diamond.
- Apply Retroguard a stain guard to help protect the polished surface.
- Apply Retropel which deters oil and chemicals from affecting polished surface.

#### **Upon completion of the polished floor DCVA agrees to:**

- Clean area for the reentry of Frito Lay employees

Polished Concrete Process [www.retroplate.com](http://www.retroplate.com) within this site is more information on the densified, guard and Retropel.

The price to polish the designated areas without dye is \$46,525.00

[landon@decorativeconcreteofvirginia.com](mailto:landon@decorativeconcreteofvirginia.com)